



## TECHNICAL DATA SHEET

**SAP No.** 30000111      **Article Description** B-E-631g/m<sup>2</sup>-1300mm

**Textile Structure** 7000068

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
2	0 °	331 g/m <sup>2</sup>	+/- 5 %	E-glass 1.200 TEX
1	90 °	288 g/m <sup>2</sup>	+/- 5 %	E-glass 600 TEX
Stitching		4 g/m <sup>2</sup>	+/- 1 %	PES (Polyester) 110 dtex SC

FURTHER CHARACTERISTICS					
Gauge	7,0	Stitching pattern	Tricot-warp	Width (nominal)	1,300 mm
Stitch length	3,50 mm	Total tolerance	5,4 %	Total areal weight	631 g/m <sup>2</sup>

**Labelling (Standard)**      Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

**Packaging (Standard)**      Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

**Storage**      With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.