



TECHNICAL DATA SHEET

SAP No. 30000124 **Article Description** U-E-1200g/m²-1300mm

Textile Structure 7000079

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
2	0 °	1,134 g/m ²	+/- 5 %	E-glass 2,400 TEX
1	90 °	54 g/m ²	+/- 5 %	E-glass 68 TEX
Stitching		12 g/m ²	+/- 3 %	PES (Polyester) 110 dtex

Fibre input can be determined individually

FURTHER CHARACTERISTICS					
Gauge	7,0	Stitching pattern	Tricot - warp	Width (nominal)	1,300 mm
Stitch length	3,50 mm	Total tolerance	5,2 %	Total areal weight	1200 g/m ²

Labelling (Standard)

Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard)

Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage

With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.