



TECHNICAL DATA SHEET

SAP No: 30000345

Article Description: Y-E-625gm²-1270mm

Textile Structure: 7000173

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)					
Layout	Construction	Areal weight		Tolerance	Material
3	0°	213	g/m ²	+/- 5 %	E-Glass 600 tex
2	45°	200	g/m ²	+/- 5 %	E-Glass 300 tex
1	-45°	200	g/m ²	+/- 5 %	E-Glass 600 tex
Stitching		12	g/m ²	+/- 3 g/m ²	PES [Polyester] 76 dtex

Fibre input can be determined individually

FURTHER CHARACTERISTICS					
Gauge	10,0	Stitching pattern	Tricot - Warp	Width (nominal)	1,270 mm
Stitch Length	2,60 mm	Total tolerance	5,4 %	Total area weight	625 g/m ²

Labelling (Standard)

Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard)

Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage

With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.