



TECHNICAL DATA SHEET

SAP No. 30000383 **Article Description** Q-E-1232g/m²-1270mm

Textile Structure 7000200

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
4	0 °	319 g/m ²	+/- 5 %	E-glass 900 TEX
3	45 °	300 g/m ²	+/- 5 %	E-glass 300 TEX
2	90 °	307 g/m ²	+/- 5 %	E-glass 600 TEX
1	-45°	300 g/m ²	+/- 5 %	E-glass 300 TEX
Stitching		6 g/m ²	+/- 1 %	PES (Polyester) 76 dtex

FURTHER CHARACTERISTICS					
Gauge	5,0	Stitching pattern	Tricot	Width (nominal)	1.270 mm
Stitch length	2.60 mm	Total tolerance	5,1 %	Total areal weight	1232 g/m ²

- Labelling (Standard)** Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.
- Packaging (Standard)** Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.
- Storage** With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.