



## TECHNICAL DATA SHEET

**SAP No:** 30000452

**Article Description:** Y-E-915gm<sup>2</sup>-1270mm

**Textile Structure:** 7000225

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)					
Layout	Construction	Areal weight		Tolerance	Material
3	0°	425	g/m <sup>2</sup>	+/- 5 %	E-Glass 1,200 tex
2	45°	242	g/m <sup>2</sup>	+/- 5 %	E-Glass 300 tex
1	-45°	242	g/m <sup>2</sup>	+/- 5 %	E-Glass 300 tex
Stitching		6	g/m <sup>2</sup>	+/- 1 g/m <sup>2</sup>	PES [Polyester] 76 dtex

Fibre input can be determined individually

FURTHER CHARACTERISTICS					
Gauge	5,0	Stitching pattern	Tricot - Warp	Width (nominal)	1,270 mm
Stitch Length	2,60 mm	Total tolerance	5,1 %	Total area weight	915 g/m <sup>2</sup>

### Labelling (Standard)

Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

### Packaging (Standard)

Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

### Storage

With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.