



## TECHNICAL DATA SHEET

**SAP No.** 30003791      **Article Description** U-C-314g/m<sup>2</sup>-1230mm

**Textile Structure** 7003892

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)				
Layer	Construction	Areal weight	Tolerance	Material
2	0 °	300 g/m <sup>2</sup>	+/- 5 %	ZOLTEK PANEX 35-13 50K
1	85 °	11 g/m <sup>2</sup>	+/- 5 %	E-glass 68 TEX
Stitching		3 g/m <sup>2</sup>	+/- 1 %	PES (Polyester) 33 dtex SC

FURTHER CHARACTERISTICS					
<b>Gauge</b>	5,0	<b>Stitching pattern</b>	Tricot	<b>Width (nominal)</b>	1.230 mm
<b>Stitch length</b>	5,00 mm	<b>Total tolerance</b>	5,3 %	<b>Total areal weight</b>	314 g/m <sup>2</sup>

### Labelling (Standard)

Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

### Packaging (Standard)

Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

### Storage

With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.