



ISO 9001 - Cert No 10490



## DYNANOTEX TECHNICAL DATA SHEET

**Product Reference:** HS 24 - 200 DLN2

Characteristics		Nominal	Tolerance	Normative
Mass per unit area	g/m <sup>2</sup>	203	± 5%	ISO 4605
Weave		Unidirectional		ISO 2113
Standard Width	mm	1000	± 3,5%	
Laminate thickness	mm	0,130	± 3,5%	(**)
Other information		Polyester fibre net		

Construction		Description			Nominal mass	Tolerance
Fibre	Layer 1	Grafil 24K 1600 dtex	g/m <sup>2</sup>	92	93%	± 3%
			%	49		
	Layer 2	Grafil 24K 1600 dtex	g/m <sup>2</sup>	92		
			%	49		
	Layer 3	Polyester fibre net	g/m <sup>2</sup>	4		
			%	2		
	Layer 4		g/m <sup>2</sup>			
			%			
Adhesive		Resin compatible			7%	± 3%

(\*\*) Theoretical thickness for an epoxy laminate with 40% of reinforcement in volume.

**Note:** Technical information furnished is based on laboratory findings and believed to be correct. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.