



TECHNICAL DATA SHEET

Product code: EWR600 (76-WVR-600-017-100-40)

Characteristics

Free of contamination Fast wet out
High laminate strength Good mechanical properties

Product code

EWR600-1000
E: E-glass
WR: woven roving
600: unit weight (g/m²)
1000: net width of fabrics (mm)

Technical data

Unit weight (g/m ²)	Warp		Weft		Moisture (%)	Loss on ignition (%)	Tensile strength on warp (N)	Tensile strength on weft (N)
	tex	Density (roving/10c m)	tex	Density (roving/10 cm)				
600 ±8%	1200 ±5%	25 ±10%	1200 ±5%	25 ±10%	≤0.2	0.4 – 0.8	≥4000	≥3850

According to the standard GB/T 18370-2001

Packaging

1. Roll packaging: Each roll is wrapped in PE film, put into a bulk carton and stacked on the pallet.
2. Pallet packaging: Each pallet stacks 16 rolls and pallets should not be stacked in more than 2 layers.
3. Typical packaging details:

Width (mm)	Weight/Roll (kg)	Roll Dimensions Ext. Ø (mm)	Rolls/Pallet	Pallet Dimension (mm)	Net Weight/Pallet (kg)
1000	42	235	16	1120 x 1120 x 135	672
1270	54	235	16	1120 x 1350 x 135	864

Storage

This product should be stored in a dry, ventilated and rainproof place, with temperatures from 5°C to 30°C and humidity between 35% and 65%. It is recommended to be kept in intact package when not used to avoid damp.